



Electronics & Identification

E2003 Proximity & Mifare Smart Card Reader

ORDERING INFORMATION

- E2003EW – EM with Wiegand
- E2003ES – EM with RS485
- E2003MW – Mifare with Wiegand
- E2003MS – Mifare with RS485

SERVICES AVAILABLE

- Technical support
- Application support
- Customization
- Guaranteed warranty

CONTACT INFORMATION

EiD Technology Sdn Bhd
7-2, Jalan USJ21/10 UEP,
47630 Subang Jaya,
Selangor. Malaysia.
Tel : 603-8023 7050
Fax : 603-8023 7052
Email : info@eid.com.my
Website : www.eid.com.my



E2003



FEATURES:

- Compact and small design.
- Audio and visual indications of LED and beep.
- Suitable for indoor/outdoor application.
- Mounting on standard single gang electrical switch box for easy installation.
- Compatible with Wiegand 34 bits and RS485 format, or user format is available.
- Self-test on reader power-up to verify the setup configuration and initialize reader operation.
- Built-in Web Server

SPECIFICATION:

- Reading distance : 5 ~ 15cm
- Response time : 300ms
- Frequency : 125KHz, 13.56MHz
- Operation Voltage : DC 12V
- Power consumption : 50mA(static), 150mA(dynamic)
- Operation Temperature : 0°C~65°C
- Operation Humanity : 5%~90%
- ESD : +/- 2.5KV
- Dimensions: 121 x 22 x 45.5 mm